


JC849 U.S. PTO  
11/22/00

11-24-00

A

Please type a plus sign (+) inside this box ➡ ⊕

PTO/SB/05 (12/97)  
Approved for use through 09/30/2000 OMB 0651-0032  
Patent and Trademark Office U S DEPARTMENT OF COMMERCE

<b>UTILITY PATENT APPLICATION TRANSMITTAL</b>  <i>(Only for new nonprovisional applications under 37 CFR 1.53(b))</i>		Attorney Docket No.	ISM/015	Total Pages	26
		First Named Inventor or Application Identifier			
		ADNAN SHENNIB			
		Express Mail Label No.	EL 114 249 586 US		
APPLICATION ELEMENTS <i>See MPEP chapter 600 concerning utility patent application contents.</i>		ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231			
<p>1. <input checked="" type="checkbox"/> Fee Transmittal Form (Submit an original, and a duplicate for fee processing)</p> <p>2. <input checked="" type="checkbox"/> Specification [Total Pages <u>14</u>] (preferred arrangement set forth below) - Descriptive title of the invention - Cross References to Related Applications - Statement Regarding Fed sponsored R&amp;D - Reference to Microfiche Appendix - Background of the Invention - Brief Summary of the Invention - Brief Description of the Drawings (if filed) - Detailed Description - Claim(s) - Abstract of the Disclosure</p> <p>3. <input checked="" type="checkbox"/> Drawing(s) (35 USC 113) [Total Sheets <u>6</u>]</p> <p>4. <input checked="" type="checkbox"/> Oath or Declaration [Total Pages <u>2</u>] a. <input checked="" type="checkbox"/> Unexecuted (original or copy) b. <input type="checkbox"/> Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed) [Note Box 5 below] i. <input type="checkbox"/> DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).</p> <p>5. <input type="checkbox"/> Incorporation By Reference (useable if Box 4b is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference herein.</p>		<p>6. <input type="checkbox"/> Microfiche Computer Program (Appendix)</p> <p>7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) a. <input type="checkbox"/> Computer Readable Copy b. <input type="checkbox"/> Paper Copy (identical to computer copy) c. <input type="checkbox"/> Statement verifying identity or above copy</p>			
		<b>ACCOMPANYING APPLICATION PARTS</b> <p>8. <input type="checkbox"/> Assignment Paper (cover sheet &amp; document(s)) 9. <input type="checkbox"/> 37 CFR 3.73(b) Statement <input checked="" type="checkbox"/> Power of Attorney (when there is an assignee) (unexecuted) 10. <input type="checkbox"/> English Translation Document (if applicable) 11. <input type="checkbox"/> Information Disclosure <input type="checkbox"/> Copies of IDS Statement (IDS)/PTO-1449 Citations 12. <input type="checkbox"/> Preliminary Amendment 13. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) (should be specifically itemized) 14. <input type="checkbox"/> Small Entity <input type="checkbox"/> Statement filed in prior application, Statement(s) Status still proper and desired 15. <input type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed) 16. <input checked="" type="checkbox"/> Other: • Cover Sheet • Express Mail Certificate</p>			
17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information: <input type="checkbox"/> Continuation <input type="checkbox"/> Divisional <input type="checkbox"/> Continuation-in-part (CIP) of prior application No.: _____/_____					
18. CORRESPONDENCE ADDRESS					
<input type="checkbox"/> Customer Number or Bar Code Label or <input checked="" type="checkbox"/> Correspondence address below (insert Customer No. or Attach bar code label here)					
NAME	Donald R. Greene 				
	Registration No. 22470 Date: November 22, 2000				
ADDRESS	Post Office Box 12995				
CITY	Scottsdale	STATE	AZ	ZIP CODE	85267-2995
COUNTRY	US	TELEPHONE	(480) 488-9895	FACSIMILE	(480) 488-5654

JC841 U.S. PTO  
09/22/00

11/22/00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: :  
:   
ADNAN SHENNIB :  
: Group Art Unit \_\_\_\_\_  
Serial No.: (to be assigned) :  
: Examiner: \_\_\_\_\_  
Filed: Herewith :

Title: INTRACANAL CAP FOR CANAL HEARING DEVICES

NEW UTILITY PATENT APPLICATION TRANSMITTAL


1. This new application is for an original utility patent, and consists of 14 pages of specification, including 4 pages of claims (25 claims, including 3 independent claims) and a 1 page abstract, plus a cover sheet and 6 sheets (10 Figures) of informal drawings.

2. The application does not yet include an executed Combined Declaration/Power of Attorney (unexecuted Declaration/Power of Attorney enclosed).

3. The inventors and their assignee (Assignment document to be filed) will be filing Verified Statements of Small Entity Status. The filing fee is calculated on a small entity basis:

CLAIMS AS FILED				
Number filed	Number extra	Rate	Basic Fee	
		(Small Entity)	\$355.00	
Total Claims	25 - 20 = 5	x \$9.00 =	45.00	
Independent Claims	3 - 3 = 0	x \$40.00 =	0.00	
Filing Fee Calculation			\$400.00	

4. No fee payment is being made at this time.

  
Donald R. Greene  
Reg. No. 22,470  
Post Office Box 12995  
Scottsdale, AZ 85267-2995  
Tel: (480) 488-9895

Dated: 11/22/2000

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: :  
:   
ADNAN SHENNIB :  
: Group Art Unit \_\_\_\_\_  
Serial No.: (to be assigned) :  
: Examiner: \_\_\_\_\_  
Filed: Herewith :

Title: INTRACANAL CAP FOR CANAL HEARING DEVICES

**EXPRESS MAIL CERTIFICATE**


Express Mail Label No. **EL 114 249 586 US**

Date of Deposit: November 22, 2000

I hereby certify that the following attached papers:

- (1) Application Transmittal, plus PTO Form PTO/SB/05;
- (2) Combined Declaration and Power of Attorney (unexecuted);
- (3) Patent Specification consisting of 14 pages including 4 pages of claims (25 claims, 3 independent claims), and 1 page Abstract; 6 sheets of informal drawing (10 Figures), plus cover sheet; and
- (4) Postcard (stamped, addressed) for acknowledging receipt.

are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above, addressed to the Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.

  
\_\_\_\_\_  
Donald R. Greene  
P.O. Box 12995  
Scottsdale, AZ 85267-2995  
Tel: (480) 488-9895  
Fax: (480) 488-5654

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**  
**APPLICATION FOR UNITED STATES PATENT**

*Title:*

**INTRACANAL CAP FOR  
CANAL HEARING DEVICES**

*Inventor:*

**ADNAN SHENNIB**  
Danville, California

*Assignee:*

**INSONUS MEDICAL, INC.**  
Newark, California

# INTRACANAL CAP FOR CANAL HEARING DEVICES

## Cross-Reference to Related Applications

This application is related to co-pending patent application Serial No. 09/327, 717, filed August 2, 1999, titled "Extended Wear Canal Hearing Device" (the "717 application"), and United States Patent No. (USPN) 6,137,889 titled "Direct Tympanic Membrane Excitation Via a Vibrationally Conductive Assembly" (the "889 patent"), each of which is assigned to the assignee of the present application.

## Background of the Invention

### Technical Field

The present invention relates generally to miniature hearing aids, acoustic and otherwise, which are fitted deeply in the ear canal.

### Description of the Prior Art

#### (1) Brief Description of the Ear Canal and Canal Hearing Aids

The external acoustic meatus (ear canal) is generally narrow and contoured as shown in the coronal view in **FIG. 1**. The ear canal **10** is an elongated cavity beginning at the canal aperture **17** and ending medially with the tympanic membrane **18** (eardrum). The cartilaginous region **11** is relatively flexible due to the underlying cartilaginous tissue. The medial (towards the tympanic membrane) part, a bony region **13** proximal to the tympanic membrane, is rigid due to the underlying bony tissue. The skin **14** in the bony region **13** is thin (relative to the skin **16** in the cartilaginous region) and is more sensitive to touch or pressure. There is a characteristic bend **15** that roughly occurs at the bony-cartilaginous junction **19** (referred to herein as the bony junction), which separates the cartilaginous **11** and the bony **13** regions. The magnitude of this bend varies among individuals. The cross section of the ear canal is generally

oval (**FIG. 2**) having a long diameter ( $D_L$ ) and a short diameter ( $D_S$ )

Hair **12** and debris **4** in the ear canal are primarily present in the cartilaginous region **11**. Physiologic debris includes cerumen (earwax), sweat, exfoliated skin and hair, and oils produced by the various glands underneath the skin in the cartilaginous region. Non-physiologic debris consists primarily of environmental particles that enter the ear canal. Canal debris is naturally extruded to the outside of the ear by the process of lateral epithelial cell migration that begins on the eardrum and extends the length of the ear canal. There is no cerumen production or hair in the bony part of the ear canal. Laterally and external to the ear canal is the concha cavity **2** and the auricle **3**, both also cartilaginous.

Conventional canal hearing aids are removed daily from the ear in order for the ear canal to “dry out” after being occluded by the hearing aid.

## (2) Review of State-of-the-Art in Canal Hearing Aid Technology

Recent advances have led to the development of extended-wear canal hearing devices, which are operated continuously deep in the ear canal for several months before removal. These deep canal hearing devices are completely inconspicuous, thus very desirable for the hearing impaired who may be concerned with the social stigma and vanity associated with wearing a visible hearing aid. For example, in the aforementioned related ‘717 application, Shennib et al. describe an extended wear canal hearing device primarily positioned in the bony part of the ear canal. The canal device in the ‘717 application is of the air-conduction type since it relies on air-conducted sounds emitted by a receiver (speaker) to excite the eardrum. Similar to other air conduction hearing aids, acoustic sealing is required for the prevention of acoustic feedback.

In the other aforementioned ‘889 patent, the hearing device is similarly positioned inconspicuously in the bony part of the ear canal. However, the excitation of the eardrum occurs via a vibrational filament which makes direct contact thereto.

These and other hearing devices of the prior art rely on water-proofing elements integrated within for protection. For example, moisture guards are incorporated onto the microphone and the receiver for protecting the transducer from the damaging effects of moisture, cerumen and water-borne debris. The coating or enclosure of the body of the device must also be water proof since water exposure (e.g., during showering, or swimming) is expected for extended-wear devices that are worn continuously in the ear canal.

However, even with water proofing means incorporated onto the device, water and water-born debris is likely to accumulate on the body of the hearing device during its long term wear causing the device to ultimately malfunction. Furthermore, water contaminants in the ear canal may accumulate around the hearing device enhancing microbial growth which leads to irritation and infections in the ear canal.

#### Review of Protective Ear Covers

Ear canal protection for applications other than hearing device wear is well known. For example, Jordan-Ross in USPN 4,916,758 discloses an ear protector for beautician use during applications of liquid treatments which may affect the ear canal. Adams in USPN 5,488,961 discloses an ear plug that is hydrophobic for allowing hearing while preventing water from entering the ear canal during swimming and other water activities. The earplug is elongated with a lumen extending along the ear canal. These and other related inventions may interfere with a hearing device worn in the ear canal and inadvertently even damage the device or injure the device wearer, because they are merely intended to protect the ear canal.

A key goal of the present invention is to provide a hydrophobic barrier for the protection of a deep canal hearing device during its extended wear in the ear canal.

Another goal of the present invention is to protect the ear canal from water and water-borne contaminants during wear of a canal hearing device.

### Summary of the Invention

The invention provides an acoustically permeative cap worn semi-permanently in the ear canal for protecting a hearing device positioned deeper within the canal. The intracanal cap conforms circumferentially to the walls of the ear canal to occlude the canal at the location of the cap. It comprises a porous membrane with pores sized to prevent water (fluids) and solid debris from entering the ear canal, and thus provides a barrier or shield against these liquid and solid contaminants from infiltrating the canal and reaching the hearing device, while allowing passage of air-conducted sounds to freely reach the microphone of the hearing device medially positioned within the canal. The protection provided by the intracanal cap thus improves reliability and longevity of the hearing device, and reduces the need heretofore required for a durable enclosure, resulting in lower cost of manufacturing for the hearing device.

In the preferred embodiment, the intracanal cap is configured separately from the hearing device. Thus, the cap can be independently inserted and removed. Alternatively, the cap may be configured attached laterally to the hearing device for positioning in the ear canal simultaneously therewith. The intracanal cap comprises a flexible ring which fits in a sealing and retaining manner along the interior walls of the ear canal. The central porous membrane is hydrophobic, to repel water coming from the outside. The canal hearing device, protected by the intracanal shield, may be of any type including acoustic output types (with a speaker), a direct tympanic drive type (with a vibrator touching the eardrum), or an electromagnetic type (with a magnet on the eardrum). The intracanal shield is preferably inserted in the deeper portion of the ear canal past the region of hair and cerumen production. For safety reasons, the insertion may be performed by a health care professional such as an otolaryngologist or an audiologist. The intracanal cap is particularly applicable for extended wear hearing devices.



### Brief Description of the Drawings

The above and still further goals, objectives, features, aspects and attendant advantages of the present invention will be better understood from the following detailed description of the best mode presently contemplated for practicing the invention, with reference to preferred  
5      embodiments and methods, and the accompanying Figures of drawing, in which:

**FIG. 1** is a side view (top) of the external ear illustrating the tortuously elongated ear canal, as described above;

**FIG. 2** is a cross sectional view of the ear canal in **FIG. 1** showing its oval cross section;

10      **FIG. 3** is a side view of a preferred embodiment of the invented canal cap which is acoustically transparent and hydrophobic for protecting a canal device medially positioned from water and debris;

**FIG. 4** is a front view of an embodiment of the invented cap showing a flexible ring and acoustically transparent, relatively flat porous membrane;

15      **FIG. 5** is an alternate embodiment of the invented cap having a bulged porous membrane;

**FIG. 6** is a perspective view of an embodiment of the invented intracanal cap made of polyurethane foam;

**FIG. 7** is a side view of the embodiment of **FIG. 6**;

20      **FIG. 8** is a view of an alternate embodiment of the canal cap attached to a lateral section of an acoustic canal hearing device used for extended wear;

**FIG. 9** is a view of the invented intracanal cap used in conjunction with a direct tympanic drive hearing device, and

25      **FIG. 10** is a view of the invented intracanal cap used in conjunction with an electromagnetic hearing aid having a magnet on the eardrum.

### Detailed Description of the Preferred Embodiments and Methods

The present invention, illustrated in **FIGS. 3-10**, provides an intracanal cap **20** which occludes the ear canal **10** and protects a canal hearing device **40** placed deep in the ear canal in proximity to the eardrum **18**. The intracanal cap **20** comprises a retention ring **21** and a porous shield **22**. The retention ring **21** conforms to the walls of the ear canal **10** when inserted within. The porous shield **22** comprises pores sized to allow incoming air-conducted sounds **50** to pass through (arrow **52**) towards the hearing device **40** and remaining medial portion of ear canal. But the pore sizes are also designed or selected to prevent fluids and solid debris from reaching the hearing device **40** and causing damage thereto. The hearing device **40** typically comprises a microphone **41** with microphone port **42**, a receiver (speaker) **43** with receiver port **44**, battery **45**, electronic components **46** and other parts not shown for clarity. A sealing retainer **47** holds the hearing device **40** in place and seals the ear canal for preventing acoustic feedback.

Incoming sounds **50** pass through the porous shield **22** of the intracanal cap **20** which may be made in various embodiments as shown in **FIGS. 4-7**. **FIG. 4** shows a diaphragm embodiment having flexible ring **21** and a relatively flat central membrane **22**. The ring is flexible to conform to the shape and size of the ear canal. An elastomeric biocompatible material such as silicone is preferably used for the ring. The ring is adhered to the porous shield via the appropriate adhesive. The thickness and pore size of the porous shield must be selected to optimize the acoustic transmission without adversely affecting the water breakthrough rating. It is understood that a thinner membrane and larger pore sizes would have better transmission of sound but with lower rating for water breakthrough. Conversely, thicker membrane and smaller pore sizes will improve the water breakthrough rating at the expense of sound transmission. Porous shields with pore sizes in the range of 1 to 10 microns and thickness in the range of 50 to 250 microns were found to be optimal for good sound

transmission. The specific combination of pore size and thickness is selected depending on the water breakthrough rating desired.

Various hydrophobic porous shield materials were tested and found to offer good results in terms of acoustic transparency (i.e., permeability) and thickness. These materials include Poseidon™ (manufactured by PALL Specialty Materials). Certain hydrophobic membranes are also oleophobic which aid in repelling earwax produced in the ear canal away from the hearing device. These membranes include ZITEX™ (manufactured by W. L. Gore & Associates, Inc.), Versapor® R and Supor® R (both manufactured by PALL Specialty Materials). These materials are typically made of acrylic copolymers, polyethersulfone polymer, and fluoropolymer. These and other materials are typically treated and supported by other materials for enhanced structure, hydrophobicity and oleophobicity.

**FIG. 5** shows an embodiment of the intracanal cap having a bulging porous shield **22**. **FIGS. 6** and **7** show an embodiment made of polyurethane foam which is inherently porous and particularly air conductive when formed thinly. The foam cap **30** is formed with a hollow cylindrical ring **31** on the perimeter and having thin porous membrane **32** at its center. The advantage of the foam cap is that it is fabricated from a single material during the manufacturing process. The intracanal cap may also be made entirely from other polymeric materials such as silicone having small perforations at its center. The perforations may be treated with hydrophobic material to enhance hydrophobicity.

The intracanal caps shown in **FIGS. 3-7** are configured separate from the canal hearing device. Thus, each cap can be inserted into and removed from the ear canal independently from the hearing device. The intracanal cap is preferably made oval in cross sectional shape, as shown in **FIG. 6**, and sufficiently flexible to assume the oval or irregular shape of the ear canal.

**FIG. 8** shows an alternate embodiment of the invented intracanal cap **20** connected to a canal hearing device **40**. Similar to the separate cap embodiment, the intracanal cap of this

embodiment comprises a retention ring **21** and a porous membrane **22** for allowing incoming sounds **50** to reach the microphone **41** of the hearing device. The attached intracanal cap allows the cap to be inserted and removed along with the hearing device **40**.

The invented intracanal cap may be used with canal hearing devices having acoustic output (speaker) as shown in **FIGS. 3** and **8**. The intracanal cap protects the hearing device and particularly its transducer mechanisms subject to damage from water and contaminants. The intracanal cap of the present invention is equally suited for hearing devices comprising alternate configurations in the ear canal. In **FIG. 9** for example, the intracanal cap **20** is used to protect a non-occluding hearing device **60** of the type described in the aforementioned '889 patent. In this hearing device configuration, a vibrating filament assembly **61** directly excites the eardrum **18**. **FIG. 10** shows yet another canal device configuration having a tympanic contact transducer of the type described in USPN 5,259,032. In this configuration, the hearing device **70** comprises an electromagnet coil **71** which vibrates a tympanic transducer **75** attached to the eardrum **18**. The tympanic transducer comprises a magnet **76** which responds to magnetic fields **72** produced by the coil **71**. The magnetic field **72** is representative of incoming acoustic signals **50**.

The intracanal cap of the present invention is not limited to the canal hearing device configurations shown in **FIGS 3** and **8-10**, but may be used with any hearing device placed deeply in the ear canal. Regardless of the configuration, the intracanal cap protects the worn hearing device, and thus improves its reliability and longevity. This protection also reduces the requirement for a protective enclosure resulting in lower cost of manufacturing for the hearing device.

The intracanal shield and the associated hearing device are preferably disposable, to be discarded once removed from the ear canal. The capping shield is preferably inserted in the deeper portion of the ear canal past the region of hair and cerumen production. For safety

reasons, the insertion is preferably made by a health care professional such as an otolaryngologist or an audiologist if the shield is to be inserted too deeply in the ear canal.

The intracanal cap is particularly suitable for use with extended wear hearing devices, in which the device operates in the ear canal continuously for several months, thus requiring protection from water and contaminants. The intracanal cap also protects the ear canal itself from water and infectious contaminants by preventing the entry of debris and contaminants into the ear canal. This debris can otherwise accumulate on and around the hearing device leading to bacterial and fungal growth in the ear canal. Furthermore, the porosity of the membrane allows for healthy air circulation in the ear canal, and in certain non-occluding device embodiments, up to the eardrum. This air circulation minimizes bacterial and fungal growth, which occurs in enclosed humid environments.

Although a presently contemplated best mode of practicing the invention has been disclosed herein by reference to certain preferred embodiments and methods, it will be apparent to those skilled in the art that variations and modifications of the disclosed embodiments and methods may be implemented without departing from the spirit and scope of the invention. It is therefore intended that the invention shall be limited only to the extent required by the appended claims and the rules and principles of the applicable law.

What is claimed is:

1           **1.**     An intracanal shield for positioning entirely in the ear canal and capping the  
2 cavity of said ear canal, comprising:

3           a conforming perimeter adapted to fit in a retaining manner along the cross sectional  
4 wall of the ear canal cavity,

5           a central porous member having pores sized for allowing air to pass through said porous  
6 member while preventing passage of fluids and solids therethrough,

7           said intracanal shield, when fitted in said retaining manner in the ear canal cavity, being  
8 positioned laterally with respect to a miniature hearing device medially positioned in close  
9 proximity to the eardrum, whereby to protect said hearing device against penetration of fluids  
10 and debris through said porous member while allowing air-borne sounds to reach said hearing  
11 device.

1           **2.**     The intracanal shield of claim 1, wherein said intracanal shield is separate from  
2 said canal hearing device for independent insertion and removal while said hearing device is  
3 positioned in-situ.

1           **3.**     The intracanal shield of claim 1, wherein said intracanal shield is attached to said  
2 canal hearing device for insertion into and removal from said ear canal along with said hearing  
3 device.

1           **4.**     The intracanal shield of claim 1, wherein said porous member is hydrophobic.

1           **5.**     The intracanal shield of claim 1, wherein said porous member is oleophobic.

1           **6.**     The intracanal shield of claim 1, wherein said porous member comprises a  
2 porous membrane.

1           **7.**     The intracanal shield of claim 1, wherein said intracanal shield is composed of  
2 disposable material for cost-effective single use of said shield.

1           **8.**     The intracanal shield of claim 1, wherein said shield is at least partially  
2 composed of polyurethane foam.

1           **9.**     The intracanal shield of claim 1, wherein said shield is at least partially  
2 composed of silicone material.

1           **10.**    The intracanal shield of claim 1, wherein said pores are sized in the range of 1  
2 to 10 microns.

1           **11.**    The intracanal shield of claim 1, wherein said intracanal shield is shaped and  
2 dimensioned to be positioned deep in the ear canal past the hair and cerumen production area  
3 therein.

1           **12.**    The intracanal shield of claim 1, wherein said intracanal shield has an oval cross-  
2 sectional shape adapted to fit comfortably in a cross section of the ear canal.

1           **13.**    A hearing system fabricated and adapted to be positioned entirely in the ear  
2 canal for extended wear, comprising:

3 a hearing device assembled and dimensioned to be medially positioned in the ear canal  
4 and,

5 an intracanal shield shaped and dimensioned to be laterally positioned with respect to  
6 said hearing device, so that said intracanal shield caps the cavity of said ear canal, said  
7 intracanal shield comprising:

8 a conforming perimeter for fitting in a retaining manner along the cross sectional  
9 wall of the ear canal, and

10 a central porous member for air ventilation with respect to said hearing device,  
11 and having pores sized to prevent penetration of fluids and solids therethrough.

1 14. The hearing system of claim 13, wherein said intracanal shield is separate from  
2 said hearing device for independent insertion into and removal from the ear while said hearing  
3 device is positioned in-situ.

1 15. The hearing system of claim 13, wherein said intracanal shield is attached to said  
2 hearing device for insertion into and removal from said ear canal along with said hearing device.

1 16. The hearing system of claim 13, wherein said porous member is hydrophobic.

1 17. The hearing system of claim 13, wherein said porous member is oleophobic.

1 18. The hearing system of claim 13, wherein said porous member comprises a  
2 porous membrane.



1           **19.**     The hearing system of claim **13**, wherein each of said hearing device and said  
2 intracanal shield is disposable.

1           **20.**     The hearing system of claim **13**, wherein said intracanal shield is at least partially  
2 composed of polyurethane foam.

1           **21.**     The hearing system of claim **13**, wherein said intracanal shield is at least partially  
2 composed of silicone material.

1           **22.**     The hearing system of claim **13**, wherein said pores are sized in the range of 1  
2 to 10 microns.

1           **23.**     The hearing system of claim **13**, wherein said hearing system is fabricated and  
2 dimensioned to be positioned deep in the ear canal past the hair and cerumen production area  
3 therein.

1           **24.**     The hearing system of claim **13**, wherein said intracanal shield has an oval cross-  
2 sectional shape adapted to fit comfortably in a cross section of the ear canal.

1           **25.**     An acoustically permeative cap shaped and dimensioned to be positioned  
2 entirely in the ear canal for extended wear therein to protect a medially positioned hearing  
3 device within the ear canal against infiltration of fluids and debris, said cap being hydrophobic  
4 and porous with pores sized to prevent fluids and solids from penetrating, but allow air-borne  
5 sound passage, therethrough into the ear canal toward said hearing device.

## ABSTRACT OF THE DISCLOSURE

An acoustically permeative intracanal cap is adapted to be worn semi-permanently deep in the ear canal for shielding a hearing device positioned deeper within the ear canal against moisture and debris infiltration. The intracanal cap conforms circumferentially to the walls of the ear canal for occlusion thereof, and comprises a porous membrane with pores sized to prevent water and solid debris from entering the ear canal while allowing air-conducted sounds to freely reach the microphone of the shielded hearing device. The intracanal cap may be entirely separate from the hearing device for independent insertion and removal, or attached to a lateral section of the hearing device for concurrent insertion and removal therewith into and from the ear canal.

ISMAPPNG 015/11070






Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10





Send correspondence to:  
Donald R. Greene  
Post Office Box 12995  
Scottsdale, AZ 85267-2995

Direct telephone calls to:  
Donald R. Greene  
Tel: 480-488-9895  
Fax: 480-488-5654

### Declaration

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

### Signature

Full name of sole inventor: Adnan Shennib

Inventor's signature \_\_\_\_\_

Date \_\_\_\_\_

Country of Citizenship: United States of America

Residence: Danville, California

Post Office Address: 243 Viewpoint Drive  
Danville, CA 94506